

## **12.1" TFT monitor for the NCR SelfServ series**



### **Serie: TFT-12-GAA**

This 12.1 inch monitor is available in standard version and has been developed for the following NCR ATM systems:

**6622 / 6625 / 6626 / 6632 / 6634**

- long life cycle due to energy-saving LED technology
- easy installation by Plug & Play



## Technical Data

### **Display: Standard**

Display size 12.1"  
Brightness 400 cd/m<sup>2</sup> (LED)  
Resolution 800 x 600 pixel (SVGA)  
Contrast 600 : 1

### **Input signal:**

Video output VGA  
H. Frequency 31 - 35 kHz  
V. Frequency 50 - 75 Hz  
Sync. signal H/V separated, TTL level  
Pixel clock max. 30 MHz  
Colours 6 bit per colours

**Adjustments (OSD):** brightness, contrast, horizontal position, vertical position, default; settings saved automatically

**Power management:** backlight is switched off by missing video signal

### **Connections:**

Input signal VGA / DVI  
Power supply 12 - 24V DC mini fit connector from ATM  
Power consumption max. 10 W

**Operating conditions:** operating temperature -10°C - +65°C

**MTBF:** backlight 50,000 hours / 25°C

**Weight:** approx. 4.5 kg (9.5 lbs)

**Scope of delivery:** 12" monitor chassis

**Manufactured acc. to:** CE compliant  
RoHS  
WEEE

**Warranty:** 24 months

**Type ref.:** 012-N0-S11-66xx

Date: 10/2018