Product information



15" TFT Monitor for WINCOR NIXDORF ProCash 28x



Series: TFT-15-GAA

This monitor can be manufactured as a standard model as well as using transflective panel technology.

The transflective model uses state-of-the-art technology replacing the high-priced Highbright / Sunlight Viewable displays that have been customary in the market so far.

The main advantage of the transflective technology is the semi-transmissive reflective filter mounted behind the LCD panel. The filter reflects the sun and daylight entering from outside and, at the same time, transmits the light produced by the LED backlights.

Instead of causing reflections, the ambient light is directly absorbed. The brighter the surroundings – the better the readability of the display!

Benefits: • energy-saving (LED)

- technology is less susceptible to wear and failure (e.g. cooling)
 thus longer service life
- transflective displays:
 no sensors to reduce brightness required
 regulates brightness by itself

Product information



Technical Data

Display:	Standard	Transflective
 Size 	15" (38cm)	15" (38cm)
Format	4:3	4:3
Type	LED-TFT	LED-TFT
Surface	matte	glossy
 Brightness 	400 cd/m ²	600 cd/m ²
Contrast	700:1	600:1
Max. resolution	1024(H) x 768(V) Pixel	1024(H) x 768(V) pixels
Max. colors	16.7 million	16.7 million
Viewing angle (H/V)	160°/140°	160°/140°
 Backlight lifetime 	50,000 h (25°C)	50,000 h (25°C)
OSD Adjustments:	auto adjustment, auto color adjustment, brightness, contrast, image and color settings	auto adjustment, auto color adjustment, brightness, contrast, image and color settings
Compatibility:	ProCash 28x	ProCash 28x


Miscellaneous:

Input signal

Connections:


Power

 Operating conditions 	operating temperature -20° - +65°C	operating temperature -20° - +65°C
 Power consumtion 	15W	15W
Dimensions (cm)	40 x 30,5 x 5 (W/H/D)	40 x 30,5 x 5 (W/H/D)
Weight	3,0 Kg	3,0 Kg
 Manufactured according to 	CE compliant, RoHS, WEEE	CE compliant, RoHS, WEEE
Warranty	24 months	24 months
(Items delivered:	mountable 15" monitor	mountable 15" monitor



VGA / DVI

12 V DC



VGA / DVI

12 V DC

Subject to errors and technical changes. Images may vary from actual product.

Date:10/2017